

Prelovšek d.o.o.

Jezero 22, 1352 Preserje, Slovenia

Tel: +386 1 363 30 86, Fax: +386 1 363 30 87, Email: info@prelovsek.si, www.prelovsek.si

GU tubes

(Glass braided sleeve with polyurethane)

| | |
|----------------------------|---|
| Characteristics | IEC 60684-3-409 |
| Material | Polyurethane and glass |
| Range of activities | -20 up to 155°C |
| Breakdown voltage | ≥ 4kV |
| Colour | Various colours (standard colour: Nature) |
| Hardness | 82 Shore A |
| Delivery packaging | Rolls, plastic spools or cut on requested length. |
| Usage | Diverse use in electromechanical industry. |

Dimensions and tolerances

| Inner diameter mm | Inner diameter tolerance mm | Wall thickness MIN mm | Wall thickness MAX mm |
|----------------------|--------------------------------|--------------------------|--------------------------|
| 0,5 | +0,3 | 0,35 | 0,65 |
| 0,8 | +0,4 | 0,35 | 0,65 |
| 1,0 | +0,4 | 0,35 | 0,65 |
| 1,5 | +0,4 | 0,35 | 0,65 |
| 2,0 | +0,4 | 0,35 | 0,65 |
| 2,5 | +0,4 | 0,35 | 0,65 |
| 3,0 | +0,5 | 0,35 | 0,65 |
| 3,5 | +0,5 | 0,35 | 0,65 |
| 4,0 | +0,5 | 0,35 | 0,65 |
| 4,5 | +0,5 | 0,35 | 0,65 |
| 5,0 | +0,5 | 0,35 | 0,65 |
| 6,0 | +0,5 | 0,35 | 0,65 |
| 7,0 | +0,5 | 0,35 | 0,65 |
| 8,0 | +0,6 | 0,5 | 0,9 |
| 9,0 | +0,6 | 0,5 | 0,9 |
| 10,0 | +0,6 | 0,5 | 0,9 |